

The MVE CryoSystem Series combines the benefits of low nitrogen consumption with mid-range vial capacity to meet the diverse needs of today's professionals worldwide. The lightweight and low-space demands of these containers make them the most economical units in their class.

## **Features Include:**

- Designed for large capacity storage
- Low liquid nitrogen consumption
- Convenient lightweight package

## Visit www.chartbiomed.com for more information.



Chart Inc. reserves the right to discontinue its products, or change the prices, materials, equipment, quality, descriptions, specifications and/or processes to its products at any time without prior notice and with no further obligation or consequence. All rights not expressly stated herein are reserved by us, as applicable

## **Tank Features**

 A	Durable, tamper-proof lid design	
B	High strength neck tube reduces liquid nitrogen loss	
C	Canisters	
D	Strong, lightweight aluminum construction	
E	Advanced chemical vacuum retention system	
F	Spider design on platform for easy retrieval and insertion of product canisters	
G	Liquid Nitrogen Reservoir	

	CryoSystem 750	CryoSystem 2000	CryoSystem 4000	CryoSystem 6000
Maximum Storage Capacity				
Number of Canisters	6	4	4	6
Number of 1.2 & 2.0 ml vials 100/box	-	2,000	4,000	6,000
Number of 1.2 & 2.0ml via 25/box	750	-	-	-
Boxes per Rack	5	5	10	10
Performance				
LN2 Capacity L	47.4	61.0	121.0	175.0
Static Evaporation Rate* L/day	0.39	0.85	0.99	0.99
Working Volume L	47	51	111	165
Normal Working Duration**, Full Days	76	38	70	104
Unit Dimensions				
Neck Opening in. (mm)	5.0 (127)	8.5 (216)	8.5 (216)	8.5 (216)
Overall Height in. (mm)	26.50 (673)	27.25 (692)	38.00 (965)	37.75 (959)
Outer Diameter in. (mm)	20 (508)	22 (559)	22 (559)	26 (665)
Weight Empty lb. (kg)	42 (19.0)	58 (26.3)	81 (36.7)	103 (46.7)
Weight Full lb. (kg)	126 (57)	182 (82.5)	300 (136)	425 (193)

\* Static evaporation rate and static holding time are nominal. Actual rate and holding time will be affected by the nature of container use, atmospheric conditions, and manufacturing tolerances.

\*\* Normal Working Duration is an arbitrary reference, to estimate container performance under normal operating conditions. Actual working time may vary due to current atmospheric conditions, container history, manufacturing tolerances and any individual patterns of use.

TWO Year Standard Warranty • THREE Year Vacuum Warranty Conforms to MDD 93/42/EEC, the Medical Device Directive for the EU.