Benchmark Baths

3 7.0

3 7.0



The Benchmark series of digital dry baths offer digital control over both temperature and time, eliminating the need for an external thermometer or timer. Available in three configurations, the digital dry baths offer capacity for up to four blocks. They are extremely space efficient. (The four block model can accommodate up to 96x1.5ml tubes in less than a square foot of bench space.)

The cavities of the high grade aluminum blocks are precision machined to match the conical size and shape of 0.5, 1.5, 2.0, 15 and 50ml tube sizes, providing unsurpassed temperature uniformity. Assorted blocks are available for compatibility with nearly all common tube sizes. Custom blocks are also available upon request, please check Benchmark's web site for a list of all available blocks.

All Benchmark dry baths offer a built-in user recalibration function, to guarantee long term temperature accuracy. Each dry bath includes an easy to use block lifter, with a temperature insulated handle for guick, convenient exchange of blocks, even while they're still hot.

- Single, double and four block capacity
- Assorted blocks for a wide variety of tube sizes

Technical Data

Temp. Range: Temp. Resolution: Temp. Accuracy: Temp. Increments: Temp. Uniformity: Timer: Dimensions (WxDxH): Single Position Two position Four Position Block Dim. (WxDxH): Chamber: **Operating Temp. Range:** Warranty Electrical:

Amb. +5 to 150 °C* 0.1°C +/- 0.2°C 0.1°C +/- 0.2°C 1 to 999 minutes

7.8x9x3.2 in./20x23x8 cm 8.7x10.3x3.2 in./22x2x8 cm 8.7 x 14 x 3.2 in./22 x 35.5 x 8 cm 3 x 3.75 x 2 in. / 7.6 x 9.5 x 5 cm Fast Heating Aluminum +4°C to +65°C 2 Years 115V AC, 60 Hz 230V AC, 50 Hz,

*Temp. range of four position dry bath is Amb. +5 to 130°C

Ordering Information

| BSH1001 BSH1002 | Benchmark Digital Dry Bath, Single Position Benchmark Digital Dry Bath, Double Position |
|--|---|
| BSH1004 | Benchmark Digital Dry Bath, Four Position |
| BSW1500 BSW1520 BSW05 BSW15 BSW50 BSW10 BSW13 BSW1516 BSW02 BSWPCR2 BSWPCR1 BSWMT | Block, 24×1.5 ml Block, $24 \times 1.5/2.0$ ml Block, 24×0.5 ml Block, 12×15 ml (block height is 3.25 in.) Block, 5×50 ml (block height is 3.25 in.) Block, 20×10 mm (or 20×2.0 ml) Block, 20×10 mm (or $20 \times 5/7$ ml) Block, 20×13 mm (or $20 \times 5/7$ ml) Block, $12 \times 15-16$ mm (or 12×10 ml) Block, 48×0.2 ml tubes or 6 PCR tube strips Block, 1×96 -well PCR Plate (for $2 \& 4$ block models) Block, 1×96 -well PCR Plate (for $1 \ $ block model) Block, $1 \times Micro Titer Plate (for 2 \ and 4 \ block models)$ |
| BSW01 | Block, solid - for slides or custom machining |
| | * To order a product in 230V, please add -230 to item number. |