

## Compact Upright Laboratory Refrigerators

**Futura Silver Series Compact Upright Laboratory Refrigerators** are designed for safe sample storage and are ideal for laboratories with limited space. These refrigerators offer superior temperature performance and sample security to ensure safe storage at uniform temperatures.

### Standard Product Features:

- Manual or Auto defrost freezer with cycle defrost refrigerator
- +39.2 °F (4 °C) refrigerator operating
- Microprocessor temperature controller
- Digital temperature display
- Audible and visual high and low temperature alarms
- White powder coat exterior
- All combination units are stacked and come with separate compressors, power cords and temperature controllers
- HFC-free refrigerant (R600a), foam insulation and packaging
- Keyed lock doors
- Magnetic door gaskets for positive seal
- Probe access ports (3/8") - one for refrigerator, one for freezer
- Pharmacy refrigerator/freezer toolkit
- 115V operation (requires two outlets)
- CDC approved power cords
- Remote alarm contacts
- Heavy duty wire shelf
- Leveling legs
- Warranty: 2 years parts and labor, 5 years compressor parts only.



LABH-21-SD



L2X-20-HG



**Hydrocarbon refrigerant** used in all LHP models



**ENERGY Star Certified** on select models



**Microprocessor Temperature Controllers**

Specifications and Ordering Information:



LHP-11-SD



LABH-15-SD



L2X-10-HG

Model	L2X-10-HG	L2X-10-SD	LHP-11-HG	LHP-11-SD	LABH-15-SD	LABH-17-SD	LABH-21-SD	L2X-20-HG	L2X-20-SD
Weight lbs	176	176	160	145	170	210	230	218	218
Exterior Height in.	60	60	59	59	73	67 3/4	74 5/8	74 5/8	74 5/8
Exterior Width in.	24	24	23 3/4	23 3/4	23 5/8	30 3/4	30 3/4	30 1/2	30 1/2
Exterior Depth in.	22	22	26 1/2	26 1/2	24 3/8	28 5/8	29	29 1/2	29 1/2
Interior Height in.	50	50	53 1/2	53 1/2	63 3/4	58 1/2	65 1/4	64 4/5	64 4/5
Interior Width in.	19 1/2	19 1/2	19 7/8	19 7/8	19	26 1/4	24 3/4	25 2/5	25 2/5
Interior Depth in.	17	17	18 3/8	18 3/8	16 3/4	20 7/8	20 3/4	22 1/4	22 1/4
Interior cu. ft.	10	10	10.5	10.5	14	17	20	20	20
# of Shelves:	5 adj	5 adj	6 adj	6 adj	6 adj	5 adj	5 adj	7 adj	7 adj
Defrost Type	Cycle								
Temperature:	+2°C to +8°C	+2°C to +8°C	+1°C to +10°C	+2°C to +8°C	+2°C to +8°C				
Plug (Receptacle)	5-15P (5-15R)								
Total Amp Draw	1.8	1.8	2.3	2.3	3	3	3	1.9	2.4
Voltage	115V, 60Hz								

Please Note: All dimensions are nominal. All specifications subject to change without notice.

